Applicant: Dick et al. Application No.: 10/688,223

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1.-38. Canceled.

39. (Previously presented) A serving wireless transmit receive unit (WTRU) for implementing transmission power control for other WTRUs wherein the serving WTRU receives data signals on an uplink dedicated channel (UL DCH) and sporadically receives data signals on an associated uplink shared channel (UL SCH), the serving WTRU comprising:

a receiver for receiving UL user data from another WTRU on an UL DCH and at least one UL SCH;

a processor for computing UL DCH target metrics based on the received <u>UL</u> user data on the UL DCH associated with the UL SCH used by the other WTRU; and

a shared channel target metric generator configured to output a respective UL SCH target metric derived from each computed UL DCH target metric for use in computing UL channel power adjustments by the other WTRU.

40. (Previously presented) The WTRU of claim 39 in which the target metrics are target signal to interference ratios (SIRs).

09/30/2008 17:07 FAX 2155686499 Volpe & Koenig 210008/0013

Applicant: Dick et al. Application No.: 10/688,223

41. (Previously presented) The WTRU of claim 40 wherein the SCHs for

which SCH target SIRs are generated are High Speed Shared Information Channels

(HS-SICHs) which operate in conjunction with High Speed Downlink Shared

Channels (HS-DSCHs).

42. (Previously presented) The method for implementing transmission

power control by a serving wireless transmit receive unit (WTRU) for other WTRUs

wherein the serving WTRU receives data signals on an uplink dedicated channel

(UL DCH) and sporadically receives data signals on an associated uplink shared

channel (US SCH), the method comprising:

receiving UL user data from other WTRUs on UL DCHs and at least one UL

SCH;

computing target metrics for UL DCHs based on the reception of signals

transmitted by a WTRU on an UL DCH associated with an UL SCH usable by the

WTRU; and

generating a respective UL SCH target metric derived from each computed

UL DCH target metric for use in computing UL channel power adjustments by the

other WTRU.

43. (Previously presented) The method of claim 42 wherein the computing

and generating of target metrics comprises computing and generating of target

signal to interference ratios (SIRs).

44. (Previously presented) The method of claim 43 wherein the SCHs for

which SCH target SIRs are generated are High Speed Shared Information Channels

- 3 -

PAGE 8/13 * RCVD AT 9/30/2008 4:05:59 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-5/43 * DNIS:2738300 * CSID:2155686499 * DURATION (mm-ss):03-58

Applicant: Dick et al. Application No.: 10/688,223

(HS-SICHs) which operate in conjunction with High Speed Downlink Shared Channels (HS-DSCHs).